

## Manual for Klångedang T1 (upgraded to rev 4)

Connections passive version:

Green in +  
Blue in -

Connections active version:

Green treble +  
Blue treble -

Yellow bass +  
White bass -

Double check connections for active version!  
Wrong connection will damage the drive units.

Adjust the spikes so the speaker is in level. Tighten then the nuts. Your dealer can advice regarding floorsavers if you want to protect the floor.



Recycled as consumer electronics.  
Complies with the EU's General Product Safety Directive

## Safety information

Klångedang T1 is not magnetically shielded, so you should not place credit cards with magnetic strips, cassette tapes, videotapes, or other magnetic storage media closer than 30cm from the speakers. For long-term storage we recommend 50 cm spacing.

If the speakers are placed where there is a risk a child or animal by accident could roll down the speakers – We recommend You prevent this by securing a safety cord with a hook attached to the back of the speaker box and the other end attached to the wall.

T1 is not intended for higher input power than 50 watts in 8 ohms, which corresponds to 20 volts effective value.

Do not switch on the amplifier before correctly connected to the speakers!

Manufactured in Sweden, under license by

Tonläget HiFi AB  
Aschebergsgatan 15  
411 27 Göteborg

Designed by: Anders Simonsson

klångedang audio



Klångedang T1 upg rev 4

Manual and safety information

Revision 19-01